

PERMATINT



Technical Data Sheet

#1055 RainSil

Water-Repellant - Concentrate/Additive
Reinforces water-repellant properties in Silicate Paint
Products. RainSil is a rain-proofing treatment for
absorbent mineral surfaces

Properties

#1055 RainSil is a clear treatment to make masonry, concrete, stucco/plaster water repellent. It is vapour permeable and reduces/inhibits the absorption of water from wind driven rain.

Where to use

#1055 RainSil silicate thinner can be added to all silicate dispersion products (1010 QuartzGuard or 1020 SiLazur) at a 1:10 ratio. #1055 RainSil can also be used on its own as is.

- Use RainSil to add extra rain-repellancy to inorganic mineral paints/stains
- Use RainSil as the final treatment overtop of previous paint coats or murals
- Use RainSil as the final anti-graffiti treatment overtop of mural paintings or silicate dispersion products

Colour

Milky white, dries clear

Coverage

Approx. 60 sq ft per L or 240 sq ft per gallon. (can vary substantially depending on surface absorbency)

Drying Time

Depending on the temperature and the relative humidity, dry to touch after approx.. 1 hr. If used on its own it should always be the final coat.

Application

Stir well before use. Do not use if the working temperature is below 5 C (40 F) or above 45 C (120 F). Apply with brush or roller. Apply an even coat and allow it to absorb into the surface.

Cleaning

Wash tools with warm water immediately after use.

Storage

Keep containers tightly sealed in a cool, dry and frost-free place. Shelf life is 12 months in unopened containers.

Safety

Keep containers sealed and out of the reach of children. DO NOT empty into drains. Let it dry out and dispose of solids with regular garbage.

Disclaimer:

All directions in this technical data sheet are given in good faith to help you to achieve the desired results. However due to unpredictable circumstances no legal liability can be based on this content. By purchasing this product, the user assumes full responsibility for testing its suitability for the intended purpose including any consequential liability arising from its use. The manufacturer's liability is limited to the replacement of faulty product.

Ingredients

Water, polysiloxane solution, stabilizer

Manufactured by: PermaTint Limited
100 Bradwick Dr., Concord, ON, L4K 1K8
www.permatint.com, info@permatint.com, 866.850.TINT (8468)